


SINGLE-SEAL EXPANSION JOINT

Wall to Wall

100 - 150 mm (4 - 6") Expansion Gaps

Maxatec 160 : A07



Expansion Joint Selection Criteria

Load Rating

Product Details

Joint Location	Gap Width B (mm)	Movement Capacity (mm)		Eurocode Rating				Product Dimensions				Product Number
		±	[Total]					Height		Sightline	Blockout	
								H1 (mm)	H2 (mm)	A (mm)	C (mm)	
Wall - Wall	100	± 50	[100]	-	-	-	-	90	-	100	100	160-A07-100
	125	± 60	[120]	-	-	-	-			125	125	160-A07-125
	150	± 75	[150]	-	-	-	-			150	150	160-A07-150

Features

Surface

Ribbed surface for greater movement

Movement

High movement capacity

Seismic movement capacity

ASTM E-1399 Class I: Thermal

Class II: Wind

Class III: Seismic

Traffic Frequency per day



- - - - -

System Options

Gap width(s)	100, 125, 150 mm
Height(s)	90 mm
Metal type(s)	Aluminium
Seal colour(s)	Black, Grey, Stone
Fire barrier	120-240 minutes
Waterproofing	Moisture barrier
Pre-assembly in factory	Contact Vexcolt Europe



SINGLE-SEAL EXPANSION JOINT

Wall to Wall

100 - 150 mm (4 - 6") Expansion Gaps

Maxatec 160 : A07

APPLICATIONS

Airport Terminals | Educational | Exhibition Centres
 Department Stores | Distribution & Retail Warehouses
 Factories | Hospitals | Museums | Offices & Hotels
 Parking | Places of Worship | Residential Buildings
 Rail, Metros & Elevated Rail Stations | Roads & Bridges
 Shopping Centres | Sports Stadiums | Supermarkets